



H2pay✓

کاتالوگ محصول

H2pay A8500



A8500


Smart Desktop Payment

Core Features

- Engaging Payment Experience
- Advanced Connectivity
- Easy Setup
- High Speed Printer
- Orderable Configurations

The A8500 SMART Desktop Payment Terminal features a 5-inch capacitive touch screen with a resolution of 1280 x 720 pixels, providing a clear and responsive interface for users. Designed to fit seamlessly into any work-space, it offers a minimal worktop footprint while incorporating smart cable and port interfaces to enhance connectivity and functionality. The terminal supports a range of connectivity options, including Ethernet at 1000 Mbps, 4G CAT4, Bluetooth 5.0, and dual-band Wi-Fi (2.4 GHz and 5 GHz), ensuring reliable and fast communication.

The A8500 is equipped with a high-speed printer that operates at 90 mm per second and accommodates a 40 mm paper roll diameter for easy paper replacement. It includes multiple ports such as USB-A, USB-C, RS232, LAN, and DC 9V, providing flexibility for various peripheral connections. Powered by Android 10, this terminal combines advanced technology with efficient performance, making it a versatile choice for modern payment environments.





A8500 Specifications	
Operating System	PayDroid based on Android 10.0
Processor	Quad-core Cortex-A53 1.6GHz
Memory	8GB FLASH+1GB DDR 16GB FLASH+2GB DDR (optional) Micro SD (TF card) up to 128GB
Card Readers	Chip & PIN Contactless Magnetic Stripe
Cameras (Optional)	0.3M Pixels Front camera
Displays	5 inch 1280 x 720 pixels capacitive touch screen
Comms Configurations	Ethernet(10/100/1000Mbps) 4G (optional) Wi-Fi® 2.4GHz&5GHz + Bluetooth® 5.0(optional)
Printer (optional)	High-speed thermal printer, Paper roll diameter: 40mm
SIM / SAM	2 Micro SAMs or 1 Micro SIM+1 Micro SAM or 2 Micro SIMs
Keys / Buttons	1 Power on/off button
Ports	With printer: 1 RS232 1 Ethernet 1 Type A USB (host) 1 Type C USB (OTG) 1 DC power Jack Without printer: 1 RS232 1 Ethernet 1 Type A USB (host) 1 Type C USB
Adapter	Input: 100-240V AC, 50Hz/60Hz Output: 9.0V DC, 1.0A Output: 5.0V DC, 2.0A (without printer version)
Physical	186 x 83 x 66 mm 334g 154 x 83 x 30 mm 251g
Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 96% Relative Humidity, Non-Condensing
Certifications	PCIPTS 6.x EMV L1&L2 EMV Contactless L1 MasterCard PayPass Visa Pay-Wave UPI qUICS American ExpressPay Discover D-PAS JCB J/Speedy Interac Flash L2 TQM CE FCC IC UL RoHS BQB